Handling Equipment



FUB 30 and FUB 60

Fit-up beds

- Designed and robustly built to withstand rugged work environments
- Fastest system to assemble 1 + 1 sections.
- One FUB set consists of one power and one idler roller bed 30T, four indepently adjustable rollers to align the two sections with each other.
- The roller bed and rollers are all mounted on one main frame.
- Tires of type Polyurethane 20.5 x 7 inch.

Ideal for:

- Wind tower fabrication
- Vessels
- Pipemills





Ordering information

FUB 30	0370 250 931
FUB 60	0370 250 932

Technical data	FUB 30	FUB 60
Max. loading capacity, ton	30	60
Min. workpiece diameter, mm (in.) at 90° included angle	610 (24)	610 (24)
Max. workpiece diameter, mm (in.) at 30° included angle	6435 (253.3)	6435 (253.3)
Roller speed, mm/min (ipm)	130-1295 (5-51)	130-1295 (5-51)
Control voltage, V DC	24	24
Mains supply, 50 Hz, 3-phase, V 60 Hz, 3-phase, V	380/400/415 400/460/480	380/400/415
Travel car bogie	yes	yes
Travel car speed, mm/min (ipm)	238-2380 (9.4-94)	240-2400 (9.5-95)
Travel car drive, AC kW	1.1	2.2
Power pack rating, kW	1.5	1.5
IP classification (motor)	IP55	IP55
IP classification (electrical)	IP43	IP43
Pump, cc	2.1	2.1
Tank capacity, I	16 (4.23)	16 (4.23)
Weight, kg (lbs.)	5250 (11575)	7360 (16226)